Premium Smooth Masonry Paint



PRODUCT DATA

Description

A high quality waterbased smooth masonry paint. Manufactured using a blend of premium quality resins for extra strength and flexibility. Provides excellent protection against adverse weather conditions. This product is part of the Flag premium range. No primer required simply thin with up to 10% water if applying on bare or absorbent surfaces.

Area of use

Exterior

Substrates

General masonry, concrete, plaster and wood etc.

Packing

5 litres and 15 litres (supplied as 3 x 5L tins)

Physical Constants

Colours: White and Magnolia (Other colours available as batch quantity

special order items)

Finish: Matt

Volume solids: 50%

Theoretical spreading rate: 8 - 12 sq. metres per litre

Flash point: N/A

Specific gravity: 1.27 – 1.29

Dry to touch: 2 hours (20°C)

Overcoating time: 4 - 6 hours

*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.

Application Details

Application method: Brush or roller

Thinner: Water Cleaning of tools: Water

Surface condition The surface should be stable, firm, dry and free of dust, sand,

loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to

application of topcoats.

Please refer to the Material Safety Data Sheet for further information. For additional guidance please contact your local Technical Sales Representative.

Please check colour before use. If using multiple cans please check batch numbers are the same.